

# STARTRAC

## ENGINE 26 S

Engine HP Category	25
Engine Type	Mitsubishi - MVS3L2
No. of Cylinder	3
Capacity (CC)	1319
Rated Speed (RPM)	2500
Cooling System	Liquid Cooled
Bore / Stroke (mm)	78/92
Max. Torque(Nm)@RPM	76.3 (Nm) @ 2000 RPM

## TYRE\*

Front	180/85D12
Rear	8.30 x 20

## TRANSMISSION

Type	Synchro Shuttle with Contact Mesh Gears
Gears	9 Forward, 9 Reverse (Including Low, Medium or High Gear)
PTO Type	Independent PTO (Wet Type)
PTO RPM	Rear 540 / Mid 2000
Steering	Hydrostatic Power Steering
Brake Type	Multi Disc Oil Immersed

## HYDRAULICS

Hydraulic System	Auto Draft Sensing & Depth Control
Lift Capacity (Kgs.)	850 (at Lower Link Point)
No. of Pumps	2
Auxiliary Hydraulics	1 DA Auxiliary Hydraulics with 2 QRCs

## SPEED & DIMENSIONS<sup>1</sup>

Speed Rounded Off (km / hr.)	20
Size LxWxH (mm)	2840 x 1140 x 2417
Wheel Base (mm)	1610
Rear Track Center (mm)	811 to 988
Weight (kg)	990

## PLATFORM

Open Station (Rear & Mid ROPS / Heater Cabin (optional) / HVAC Cabin (optional))

Note: Products undergo continuous upgradations. Hence, above mentioned specifications are subject to change without prior notice. #4- 5% Tolerance variations. \*Other tyre options also available.

## LOADER

**INNOVATION**  
SHOCK ABSORBER

*STARTRAC LOADER* specifically designed to maximize the performance of the front loader and tractor. They offer a high lifting capacity, perfect for landscaping or light utility work. The Startrac Loader operates with single joystick control and has quick & easy attachment and detachment of bucket.

**500 KG**  
LIFT  
CAPACITY



Also Available Different Types of Attachments



Standard / Heavy Duty Bucket



Bucket with Grabber



4 in 1 Bucket



Pallet Fork

# STARTRAC

EU HOMOLOGATED TRACTOR MODELS

Your **STAR** Performer



Powered by

**MITSUBISHI**  
DIESEL ENGINE

www.startractors.com

**STAGE V**

9+9 SYNCHRO SHUTTLE

MODEL	STARTRAC 22	STARTRAC 26	STARTRAC 26H	STARTRAC 26 MID ROPS	STARTRAC 26H MID ROPS
-------	-------------	-------------	--------------	----------------------	-----------------------


ENGINE	STARTRAC 22	STARTRAC 26	STARTRAC 26H	STARTRAC 26 MID ROPS	STARTRAC 26H MID ROPS
Engine HP Category	22	25	25	25	25
Engine Type	Mitsubishi L3E Stage - V	Mitsubishi MVS3L2 Stage - V	Mitsubishi MVS3L2 Stage - V	Mitsubishi MVS3L2 Stage - V	Mitsubishi MVS3L2 Stage - V
No. of Cylinder	3	3	3	3	3
Capacity (CC)	953	1319	1319	1319	1319
Rated Speed (RPM)	3000	2500	2500	2500	2500
Cooling System	Liquid Cooled	Liquid Cooled	Liquid Cooled	Liquid Cooled	Liquid Cooled
Bore / Stroke (mm)	76/70	78/92	78/92	78/92	78/92
Max. Torque(Nm)@RPM	52 (Nm) @ 2000 RPM	76.3 (Nm) @ 2000 RPM	76.3 (Nm) @ 2000 RPM	76.3 (Nm) @ 2000 RPM	76.3 (Nm) @ 2000 RPM

TRANSMISSION	STARTRAC 22	STARTRAC 26	STARTRAC 26H	STARTRAC 26 MID ROPS	STARTRAC 26H MID ROPS
Type	Sliding Mesh : Side Shift Gear Levers	Sliding Mesh : Side Shift Gear Levers	Hydrostatic	Sliding Mesh : Side Shift Gear Levers	Hydrostatic
Gears	9 Forward, 3 Reverse (Options-Low, Medium or High Gear)	9 Forward, 3 Reverse (Options-Low, Medium or High Gear)	3 Forward / 3 Reverse (Options-Low, Medium or High Gear)	9 Forward, 3 Reverse (Options-Low, Medium or High Gear)	3 Forward / 3 Reverse (Options-Low, Medium or High Gear)
PTO RPM	540 & 540 E	540 & 540 E	Rear 540 / Mid 2000	540 & 540 E	Rear 540 / Mid 2000
Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
Brake Type	Multi Disc Oil Immersed	Multi Disc Oil Immersed	Multi Disc Oil Immersed	Multi Disc Oil Immersed	Multi Disc Oil Immersed

HYDRAULICS	STARTRAC 22	STARTRAC 26	STARTRAC 26H	STARTRAC 26 MID ROPS	STARTRAC 26H MID ROPS
Hydraulic System	Auto Draft Sensing & Depth Control (2 Levers)	Auto Draft Sensing & Depth Control (2 Levers)	Precision Control	Auto Draft Sensing & Depth Control (2 Levers)	Precision Control
Lift Capacity (Kgs.)	850 (at Lower Link Point)	850 (at Lower Link Point)	900 (at Lower Link Point)	850 (at Lower Link Point)	900 (at Lower Link Point)
No. of Pumps	1 (for Steering & Hydraulic System with Priority Valve)	2 (One for Hydrostatic Steering & other for Hydraulic System)	2 (Total 28 LPM)	2 (One for Hydrostatic Steering & other for Hydraulic System)	2 (Total 28 LPM)
Auxiliary Hydraulics	Trailer Hydraulic Tipping Single Outlet Standard <b>Optional Kit available :</b> 1 DA Auxiliary Hydraulics with 2 QRCs or 2 DA Auxiliary Hydraulics with 4 QRCs	1DA Auxiliary Hydraulics with 2 QRCs <b>Optional Kit available :</b> Extra Secondary DA Auxiliary Hydraulics with 2 more QRCs	1DA Auxiliary Hydraulics with 2 QRCs <b>Optional Kit available :</b> Extra Secondary DA Auxiliary Hydraulics with 2 more QRCs	1DA Auxiliary Hydraulics with 2 QRCs <b>Optional Kit available :</b> Extra Secondary DA Auxiliary Hydraulics with 2 more QRCs	1DA Auxiliary Hydraulics with 2 QRCs <b>Optional Kit available :</b> Extra Secondary DA Auxiliary Hydraulics with 2 more QRCs



Next Generation Styling



Hydrostatic Power Steering



Engine : Stage V Mitsubishi 3 Cylinder



Ergonomic Seating & Footboard Area



Front Opening Bonnet



Powerful Hyd. Lifting Capacity

TYRE OPTIONS	Agriculture	Turf	Industrial (Flotation)	Agricultural Wide Plus	Agrimax Turf RT 333 Garden	Wider F - Agri	Industrial (Regular)	Basic Agri
Front	180/85D12	23 x 8.5 - 12	23 x 8.5 - 12	180/85D12	240/60R12	23 x 8.5 - 12	23 x 8.5 - 12	5.00 x 12
Rear	8.30 x 20	33 x 15.5 - 16.5	33 x 15.5 - 16.5	280/70R20	320/65R18	280/70R18	12 x 16.5	8.00 x 18
<b>STARTRAC 22</b>								
Max. Speed Rounded Off (km/hr)	24	22	22	24	23	22	22	21
Size L x W x H (mm)	2700 x 1080 x 2100	2700 x 1390 x 2050	2700 x 1390 x 2050	2700 x 1167 x 2095	2700 x 1220 x 2080	2700 x 1220 x 2060	2700 x 1264 x 2050	2700 x 1050 x 2060
Wheel Base (mm)	1480	1490	1490	1490	1490	1490	1490	1490
Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	883 to 988	845 to 988	939	743 to 988
Weight (kg)	900	942	970	931	931	906	944	879
<b>STARTRAC 26</b>								
Max. Speed Rounded Off (km/hr)	20	18	19	20	19	18	19	18
Size L x W x H (mm)	2700 x 1080 x 2100	2700 x 1390 x 2050	2700 x 1390 x 2050	2700 x 1167 x 2095	2700 x 1220 x 2080	2700 x 1220 x 2060	2700 x 1264 x 2050	2700 x 1050 x 2060
Wheel Base (mm)	1490	1490	1490	1490	1490	1490	1490	1490
Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	883 to 988	845 to 988	939	743 to 988
Weight (kg)	950	992	1020	981	981	956	994	929
<b>STARTRAC 26H</b>								
Max. Speed Rounded Off (km/hr)	0 to 22	0 to 21	0 to 21	0 to 22	0 to 21	0 to 21	0 to 21	0 to 20
Size L x W x H (mm)	2780 x 1140 x 2200	2780 x 1490 x 2147	2780 x 1490 x 2153	2780 x 1167 x 2181	2780 x 1270 x 2167	2780 x 1220 x 2154	2780 x 1264 x 2161	2780 x 1140 x 2171
Wheel Base (mm)	1550	1550	1550	1550	1550	1550	1550	1550
Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	951 to 988	883 to 988	939	811 to 988
Weight (kg)	1035	1077	1105	1066	1066	1041	1079	1014
<b>STARTRAC 26 MID ROPS</b>								
Max. Speed Rounded Off (km/hr)	20	18	19	20	19	18	19	18
Size L x W (mm)	2700 x 1080	2700 x 1390	2700 x 1390	2700 x 1167	2700 x 1220	2700 x 1220	2700 x 1264	2700 x 1050
Height - with Front ROPS UP (mm)	2190	2140	2140	2185	2170	2150	2140	2150
Height - with Front ROPS Folded Down (mm)	1474	1424	1424	1469	1454	1434	1424	1434
Wheel Base (mm)	1490	1490	1490	1490	1490	1490	1490	1490
Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	883 to 988	845 to 988	939	743 to 988
Weight (kg)	1008	1050	1078	1039	1039	1014	1052	987
<b>STARTRAC 26H MID ROPS</b>								
Max. Speed Rounded Off (km/hr)	0 to 22	0 to 21	0 to 21	0 to 22	0 to 21	0 to 21	0 to 21	0 to 20
Size L x W (mm)	2780 x 1140	2780 x 1490	2780 x 1490	2780 x 1167	2780 x 1270	2780 x 1220	2780 x 1264	2780 x 1140
Height - with Front ROPS UP (mm)	2280	2237	2243	2271	2257	2244	2251	2261
Height - with Front ROPS Folded Down (mm)	1476	1423	1429	1457	1443	1430	1437	1447
Wheel Base (mm)	1550	1550	1550	1550	1550	1550	1550	1550
Rear Track Center (mm)	811 to 988	980 to 1080	980 to 1080	883	951 to 988	883 to 988	939	811 to 988
Weight (kg)	1093	1135	1163	1125	1125	1099	1137	1072